

Parameters of the 3T floor lifting system



High-precision hydraulic transmission, smooth movements, easy operation, low failure rate; High-strength chain pulling without extension, long lifespan, high safety factor; Double-chain lifting, safe and reliable; With adjustable screw to ensure the levelness of the platform, stability of lifting and lowering; With large capacity pump pack, realizing high lifting speed and low operating noise; Aesthetic design, durable structure; Widely used in the 4S shop, repair shop and other large-scale users, for a vehicle lifting, and

cargo lifting or vehicle parking as well.

serial no.	item	technical parameters, etc.	remarks
1.	product no.	QSJY3-4B	
2.	brand	HOTON	
3.	product name	Fixed-type four post lifting platform	
4.	rated lifting capacity	3000kg	
5.	size	6000*3500mm	
6.	Max lifting height	length/wi dth/hei ght: 6000/3500/5500	
7.	mi n height	≤200	
8.	ri sing speed	3m-4m/mi n	
9.	lowering speed	3m-4m/mi n	adjustable
10.	motor power	4kw	
11.	voltage for power pack	380v	
12.	lifting mode	double-chain hydraulic lifting	
13.	Hydraulic oil model	Changcheng summer 46#、winter 32#	self supply
14.	Max lifting control	limit switch	
15.	Max lifting failure remedy	double limit switches	
16.	system control mode	electric-controlled	
17.	Power configuration	24v	
18.	outer paint	Audi Grey	
19.	package size	columns : 6000/460/400mm*2 ° control cabinet : 750/520 ° platform: 6000/1500/500mm	7CBM/2800kg





