

Complete List of Equipment/Tools for Auto-Repair Shop

| S/N | Name | Brand | Model | Quantity | RMB PRICE | price/FOB SHANGHAI | Amount | Ref. Picture | Parameters |
|------------------------------------|-----------------------------------------------------|---------|-------------------|----------|-----------|--------------------|-----------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Universal Servicing Machine | | | | | | | | | |
| 1 | 30T shop press | HOTON | 30T | 1 | 2150 | \$311.6 | \$311.6 |  | 30T SHOP PRESS WITH GAUGE RATED LOAD: 30T STROKE: 150mm MAX.WORKING DISTANCE: 820mm MIN.WORKING DISTANCE: |
| 5 | Air Compressor | HOTON | 1.0/8 | 1 | 3980 | \$576.8 | \$576.8 |  | Press:8kg Displacement:1.05M3 Power:7.5KW、380V With Air Tank:300L |
| 18 | Drilling machine | JinDin | 16mm | 1 | 1485 | \$215.2 | \$215.2 |  | Work area: 270×280mmbottom area: 254×237mmhigh 1230mm Power: 750w |
| 7 | HC/C2H2 PC | BESTIR | 6PC | 2 | 550 | \$79.7 | \$159.4 |  | Includes lists, pipes, gun every two |
| 8 | Oil-Water Shifter | HOTON | C002 | 3 | 550 | \$79.7 | \$239.1 |  | C glass is used in pipeline H glass is used in Paint Baking House |
| 3 | cool dryer machine | Hoton | 0.9/8 | 1 | 780 | \$113.0 | \$113.0 |  | cool dryer machine. 0.9/8 |
| 4 | Grinding machine220V/50HZ | JinDin | 200MM | 1 | 395 | \$57.2 | \$57.2 |  | Grinding diameter of 200 (mm) rated speed multiple (R / min) Input power of 380 (W) 220Vsecurity line speed multiple (M / s) |
| 5 | Vise | HG | 200mm | 1 | 420 | \$60.9 | \$60.9 |  | 200MM |
| H2202 | Containing 330 fast repair and maintenance tool kit | BESTIR | 6663 | 4 | 3988 | \$577.97 | \$2,311.9 |  | Containing 330 fast repair and maintenance tool kit |
| 8 | parts box | Feiyong | FY903 | 4 | 320 | \$46.4 | \$185.5 |  | parts box,Three. |
| 9 | AIR PIPE ROAD PVR | HOTON | 500M ² | 1 | 8000 | \$1,159.4 | \$1,159.4 |  | Air system, PVR pupe, Main line is 40mm,Branch line is20mm,stick, 120m main pipe |

| | | | | | | | | | |
|------------------------------------|---------------------------------------|---------|----------------|----|-------|-----------|-----------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10 | Carry lift | NUOLI | 2T | 1 | 1650 | \$239.1 | \$239.1 |  | 2T, carry car |
| H224 | tool cabinet | HOTON | JS326 | 1 | 1145 | \$165.94 | \$165.9 |  | 780*465*820MM 6 draw: 545*395*45mm 63kg |
| H225 | part cabinet | HOTON | JS500 | 1 | 1180 | \$171.01 | \$171.0 |  | 660*450*1540MM 57kg |
| H231 | Workbench | FLYTECH | FY800LS | 1 | 2444 | \$354.20 | \$354.2 |  | FY800LS Stainless Steel Tabletop 1900x910x780(mm) |
| H350 | long light (for workshop) | HOTON | 10cm*5cm*480cm | 6 | 700 | \$101 | \$608.7 |  | Using LED lights, 10*5*480cm material aviation aluminum + light diffusion PC cover + connector |
| H355 | arrow light (for workshop) | HOTON | 1.2*2 | 10 | 150 | \$22 | \$217.4 |  | Using LED lights, 1.2m*2, material aviation aluminum + light diffusion PC cover + connector Mainly used for fine washing |
| 53 | Honeycomb light (for wash and polish) | HOTON | 1bay/7*4m | 4 | 1450 | \$200.0 | \$800.0 |  | Using LED lights, each 0.6m, 8w, material aviation aluminum + light diffusion PC cover + connector Mainly used for fine washing |
| 34 | Honeycomb light (for wash and polish) | HOTON | 1bay/7*4m | 1 | 968 | \$140 | \$140.3 |  | Using LED lights, each 0.6m, 8w, material aviation aluminum + light diffusion PC cover + connector Mainly used for fine washing |
| 18 | Light drum drum integration | HOTON | 12M/12m | 4 | 1800 | \$260.9 | \$1,043.5 |  | Light&Electronic line role drum integration |
| Equipment of Servicing Shop | | | | | | \$0.0 | \$0.0 | | |
| 1 | 3D Four Wheel Alignment Machine | HOTON | HC3D-808 | 1 | 19800 | \$2,869.6 | \$2,869.6 |  | Two 3D digital camera, four goals target, equipment calibration only once the installation is complete, without periodic repetition, dynamic measurement, the low level of demand for lift, precision range measurements |
| 2 | Lifter for wheel alignment(four legs) | HOTON | HC440W | 1 | 14800 | \$2,144.9 | \$2,144.9 |  | Capacity:4T /1.7m Power:2.2KW/380V 1.mainly used for mini bus,2.accurate horizontal and adjustable,applicated in kinds of wheel aligner |

| | | | | | | | | | | |
|-----------|----------------------------------------------|--------------|---------------|---|-------|-----------|-----------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| L205 2 | Two Post Lift (single release) | LAUNCH | TLT245SC S | 4 | 7250 | \$1,050.7 | \$4,202.9 |  | Manual single lock release Rated load: 4500kg Lifting height: 1850mm Initial height: 110mm Lifting time: 50s Lowering time: 20s 40s Passing width for symmetric installation: 2880mm | 375×60×69 287×16×14 34×24×80CM 102×36×20 |
| 4 | Dynamic Wheel Balancer (No Cave) | HOTON | ZH825B | 1 | 3150 | \$456.5 | \$456.5 |  | Max.wheel weight:65kg Power: 0.2KW Voltage:220V,Accuracy:±1g, Average Speed:220rpm,wheel dia.:10"-24",wheel width:1.5"- 20" | |
| ##### | 24" Tire changer right help arm | HOTON | ZH650R | 1 | 6578 | \$953.3 | \$953.3 |  | Rim clamping from outside: 10" -20" Rim clamping from inside: 12"-24" Bead-breaker force: 2500kg Max.wheel diameter: 41"(1040mm) Wheel width: 3" - | |
| H2032 | Rotary Chassis Noise Detector 3.5T manual | HOTON | X35R | 1 | 13500 | \$1,956.5 | \$1,956.5 |  | With rotary V head Lift weight: 3500kg voltage: 380v3phase/220v 1phase power: 2.2kwX2 height: 1100mm single duration: 1042HZ temperature: 3050°C Net weight: 660kg | |
| H1206 | Tire inflation machine(06.8kg) | FLYSPE ED | FS301 | 1 | 1250 | \$181.2 | \$181.2 |  | Max E51 Specifications Power supply 220V/50~60Hz Operating pressure range 0~6.8bar (0~99psi) Default pressure value 2.2bar (32psi) Reading accuracy + 1 psi Operating temperature 10 ~ 50°C Weight 9kg | |
| 7 | Oil-sucking Machine | HOTON | 3197L | 1 | 950 | \$137.7 | \$137.7 |  | Vacuum tech.,measuring cup:12L,oil tank:80L,use for replacing oil | |
| 3 | Brake drum&disc machine | Longshan | C9335 | 1 | 8580 | \$1,243.5 | \$1,243.5 |  | Range of Processing Diameter 180-350 Brake Drum 180-350 Brake Disc180-350 Rotating Speed of Work-piece (r/min) 90 Max. Travel of Tool (mm) 100 Overall Dimensionsmm (L x W | |
| H234 | Battery Charger/Booster | FLYTECH | FY1400 | 1 | 1690 | \$236 | \$236.4 |  | INPUT VOLTAGE: 220V &380 50HZ/60HZ POWER: 1.4kw CHarge voltage: 12/24V charge current: 11/17/24/31/38/50A charge start current: 1250A | |
| 9 | Gear oil filling machine | GREEN | VX500 | 1 | 600 | \$87.0 | \$87.0 |  | 1) pressor:1-2.5bar, 2) weight: 18.5kg, 3) volumn: 24L, 4) The maximum pressure safety valve: 4bar, 5) medium: oil, gear oil, the use of international advanced technology and design, long | |
| 27 | ATF Oil Replacing Machine computer LED | shuangying | ATF6800 | 1 | 3980 | \$576.8 | \$576.8 |  | power:0.18KW,AC220V50Hz/ DC12V,weight:40Kg,size:430*5 40*1080mm(L/W/H),double line design,new oil and used oil are totally seperated,100% renew,above 5 bar pressure,high efficiency,reliable | |

| | | | | | | | | | | |
|-----------|-----------------------------------------------|--------|---------------|---|-------|-----------|-----------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| L300 2 | VALUE300 refrigerant machine | LAUNCH | Value300 | 1 | 8600 | \$1,246.4 | \$1,246.4 |  | 1. Nondisassembly maintenance that save time and effort, and reduce accessories loss 2. Automatic full service without manual intervention 3. Accurate recharging with built-in automotive A/C database that covers mainstream models 4. Visible operation steps with | 135x66x72cm |
| H2045 | Brake oil exchanger (air press) | HOTON | GS432 | 1 | 1250 | \$181.2 | \$181.2 |  | Power source (driving force): pneumatic air Working pressure (pressure): 060PSI Weight (weight): 10kg Dimensions (size): 370 * 260 * 750 Scope (range): small gasoline and diesel vehicles | |
| L300 7 | Injector Cleaner & Tester(GDI) | LAUNCH | CNC801 GDI | 1 | 2980 | \$431.9 | \$431.9 |  | Brand Name: LAUNCH Size: 500*600*700MM Product name: Car Wash Machine Voltage: 220240V Package size 45x45x50 Package weight 28kg | 54*52*58 |
| 11 | Assembly Lifting and Handling Machine | HOTON | H2054 | 1 | 950 | \$137.7 | \$137.7 |  | Capacity:2T Lowest330mm/Highest2560m m,Gross weight:55kg | |
| 12 | gear bracket | HOTON | H2057 | 1 | 950 | \$137.7 | \$137.7 |  | Capacity:0.5t lowest870mm/highest1800mm ,size:780*730*910 | |
| L230 3 | LH2303 3T low position double pump jack | LAUNCH | LH2303 | 1 | 498 | \$72.2 | \$72.2 |  | Rated load: 3000kg Lifting height: 505mm Initial height: 75mm Package:80x38x20cm Weight:34.2kg One pallet:18pc | 80x38x20cm |
| 14 | Spring Disassembling(press type) | HOTON | H2011 | 1 | 950 | \$137.7 | \$137.7 |  | easy operating for one worker,adjust in many directions,reliable | |
| 32 | Parts Washer | HOTON | VX3000 | 1 | 2695 | \$390.6 | \$390.6 |  | Disassembled parts can be flushed and cleaned | |
| 35 | engine flip rack | HOTON | 500KG | 1 | 1350 | \$195.7 | \$195.7 |  | Worm with oil pan | |
| 15 | working lamp assy. | QS | 12M | 6 | 260 | \$37.7 | \$226.1 |  | high reliability, 15m | |
| 16 | working air assy. | QS | 12M | 6 | 260 | \$37.7 | \$226.1 |  | high reliability12m/8mm | |
| HL31 6 | 1/2 pneumatic wrench | HOTON | HL316 | 1 | 320.0 | \$46.38 | \$46.4 |  | 1/2 1020NM/2.7KG | |

| | | | | | | | | | |
|-------------------------------------|-------------------------------------------------------------------------------|--------|--------------|----|-------|-----------|-----------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| R680 | torque wrench (charge) | HOTON | R680 | 1 | 360 | \$52.17 | \$52.2 |  | 1/2—/350NM 2x20v 4.0battery |
| 22 | TPMS tester | LAUNCH | TPMS501S | 1 | 550 | \$79.7 | \$79.7 |  | Features Covers over 98% global vehicles with tire pressure system. ★Activate and match with |
| 23 | LTR03 RF Sensor | LAUNCH | LTR03 | 40 | 65 | \$9.4 | \$376.8 |  | Features 1. Compatible with over 98% of OElevel sensors in 315MHz and 433MHz. |
| L100 5 | Auto Tester | LAUNCH | X431PAD v | 1 | 10500 | \$1,521.7 | \$1,521.7 |  | 10.1 inch LCD screen, ECU programmer 2 Year free update Package: 43x36x36cm Weight 10kg |
| 51 | VSP-310 Air Conditioning Cleaning Endoscope 2-in-1 | LAUNCH | VSP310 | 1 | 748 | \$108.4 | \$108.4 |  | VSP-310 Air Conditioning Cleaning Endoscope 2-in-1 |
| 53 | BST-500 domestic standard configuration | LAUNCH | BST500 | 1 | 437.8 | \$63.4 | \$63.4 |  | BST-500 domestic standard configuration |
| H2615 | 28件多功能水箱压力表组 28PCS Radiator Pressure Tester vacuum-type Cooling system Kit | HOTON | H2615 | 1 | 496 | \$71.88 | \$71.9 |  | 28件多功能水箱压力表组 (塑钢) 28PCS Radiator Pressure Tester vacuum-type Cooling system Kit |
| H2605 | TU-443多功能燃油表 TU-443 Fuel injection pressure gauge | HOTON | H2605 | 1 | 330 | \$47.83 | \$47.8 |  | TU-443多功能燃油表 TU-443 Fuel injection pressure gauge |
| 21 | Oil/Transmission Pressure tester | HOTON | TU-12 | 1 | 180 | \$26.1 | \$26.1 |  | <ul style="list-style-type: none"> • 3-1/2" gauge • Scales read 0-28Kg/cm2 (0-400Psi) • Both English and metric scales • Kit includes adapters of all popular applications |
| 22 | Compression Testers | HOTON | TU-003 | 1 | 135 | \$19.6 | \$19.6 |  | A convenient push-button release valve provides for re-checking cylinder compression without removing the gauge. Adapters threaded 14mm, 14mm (long reach) and 12mm. |
| 23 | Vacuum degree tester | HOTON | TU-003 | 1 | 90 | \$13.0 | \$13.0 |  | Vacuum degree tester |
| 24 | Manual vacuum pump | HOTON | PK9014 | 1 | 350 | \$50.7 | \$50.7 |  | Manual vacuum pump |
| Equipment for Painting Plant | | | | | | \$0.0 | \$0.0 | | |

| | | | | | | | | | |
|-------------------------------------|---------------------------------------------------|---------|-----------|----|-------|-----------|-----------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Painting& Baking Machine | HOTON | ZD280 | 1 | 44500 | \$6,449.3 | \$6,449.3 |  | Lamp heater,Two fan(2 INLET), low threshold within one meter outside and inside, LED lamp Outside Size (mm):7000×5200×3370 Front Door(mm):3000(w)×2600(H)Inside Size(mm):6900×3900×2650 |
| 2 | Heating Lamp(3 tube) | Feiyang | FY3AL | 1 | 1750 | \$253.6 | \$253.6 |  | single phase/220V/50Hz Rated Power:3KW,adjustable height:0.15-2.1m,pre-heating:1-15min,baking:0-30min,working distance:0.3-0.5m ,area:0.8*1m,with quartz tube |
| 3 | Spray gun | jinli | 63SS | 1 | 1050 | \$152.2 | \$152.2 |  | standard 0.6L plastic paint tank,nickel plating gun body,stainless pin and nozzle,adjust the painting area,output qty. and inlet |
| 4 | Polishing Machine | DEWALT | DW849 | 1 | 1150 | \$166.7 | \$166.7 |  | powerful motor,ball bearing style,long life,Electronic Speed Control module can insure the set speed |
| Equipment for Body Repairing | | | | | | \$0.0 | \$0.0 | | |
| 1 | Body Rectifying Machine | HOTON | M5 | 1 | 25800 | \$3,739.1 | \$3,739.1 |  | working plate size(L/W/H)5400mm*2100mm*500mm working pressure of hydraulic system:70Mpa,Max push force:100KN,working area:360° Air Source |
| 2 | spot welding machine | Feiyang | FY6000 | 2 | 2350 | \$340.6 | \$681.2 |  | multi-position of welding,can be choosed freely,precise time adjusting system,function of spot welding in two sides is optional |
| 3 | CO2 welding machine | Feiyang | FY4200 | 1 | 3450 | \$500.0 | \$500.0 |  | input voltage:380V,welding current:35A-250A,applicable wire:0.8-1.0-1.2mm |
| 4 | separate style jack | SQL | 4T | 1 | 1050 | \$152.2 | \$152.2 |  | imported hydraulic sealing parts,max. output pressure:65MPa, stoke length:127mm,capacity4T,ten d:1360mm,max.pressure of oil |
| 5 | Pneumatic Polishing Machine | DR | DR301 | 1 | 530 | \$76.8 | \$76.8 |  | Chassis size ... 125 mm Vibration gauge ... 5 mm No load rotational speed ... 9000 rpm Weight... 1.1 kg Air consumption ... 0.38 |
| Cleaning Machine | | | | | | \$0.0 | \$0.0 | | |
| 9 | Finely cleaned floor grille (for wash and polish) | HOTON | 1bay/7*4m | 28 | 65 | \$9.4 | \$263.8 |  | 4x7m 8 tons under pressure, light weight, detachable, easy to install, no tools to build quickly, no slot above 3cm thickness, widely used in 4S booth, car beauty shop, foil |

| | | | | | | | | | |
|---------------------|---------------------------------------------------------------------|---------|---------------------|----------|-------|-----------|-------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Body Cleaning Machine | JEEPLUS | T318 | 1 | 1980 | \$287.0 | \$287.0 |  | pressure:80bar ,power:0.75kw,water outlet:12L/min. |
| 2 | dust&fouling removing machie | Chaobao | CB30L | 1 | 320 | \$46.4 | \$46.4 |  | 30L,Power:0.75KW |
| 3 | Foam Machie | HOTON | 80L | 1 | 450 | \$65.2 | \$65.2 |  | Pressure:2-3kg,capacity:80L |
| EV CAR EQUIPMENT | | | | | | \$0.0 | | | |
| L1206 | EVT501 battery leak tester | LAUNCH | EVT501 | 1 | 6800 | \$985.5 | \$985.5 |  | Power:20W (Max) Test Pressure Range: 0~30Kpa Sensor Resolution:1Pa Test Accuracy:±5Pa Data Storage Method Internal |
| L1211 | New energy battery test pack | LAUNCH | BATTERY PACK | 1 | 2950 | \$427.5 | \$427.5 |  | It supports reading the current soc/soh of the battery pack, unit / module voltage, input / output current and power, battery temperature, as well as reading the detailed status information and fault |
| E54014 | Lithium Battery Module Capacity Charging and Discharging Integrated | BESITA | E54014 | 1 | 12600 | \$1,826.1 | \$1,826.1 |  | 1. Voltage input range: 2VDC~110VDC. 2. Discharge current: adjustable from 1 to 60A, with a step size of 1A. 3. Voltage detection |
| E54012 | 24-cell Li-ion Smart Balancer (20A with Built-in Charging) | BESITA | E54012 | 1 | 11250 | \$1,630.4 | \$1,630.4 |  | 1. Support 2-24 series lithium battery balancing. 2. Balanced current: adjustable from 1-20A. 3. Accurately collect battery voltage |
| E683 | (6837) 48 New Energy Tool Solutions | BESITA | E6837 | 1 | 2760 | \$400.0 | \$400.0 |  | 6837A 20 piece insulation screwdriver tool holder set 6837B 27 piece insulation pliers tool holder set |
| 1215 | EV Battery Lift | HOTON | E1215D | 1 | 7980 | \$1,156.5 | \$1,156.5 |  | Maximum lifting capacity: 1200kg Maximum lifting height: 1850mm Minimum lifting height: 550mm Tabletop length: 1500mm Countertop width: 800mm |
| maintaince set tool | | | | | | | | | |
| 1 | Mechanic Bit Repair Tool | | SEE SHEET2 | 1 | | \$3,628 | \$3,628.0 | | See the list sheet 1 |
| | | | | | | 合计 | \$52,924.8 | | |

Shanghai HOTON Auto equipment, FOB shanghai 02159159353 13801993101 CONTACT:MR John, 1PC 40 CONTAINER